

XHD DUCTape™

10 MIL UTILITY DUCT TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Polyester (PET) cloth / polyethylene (PE) film with an aggressive natural rubber pressure sensitive adhesive provides a quality utility product. Conformable to irregular surfaces.

PRODUCT APPLICATION

Packaging, wrapping and sealing, binding and bundling and general maintenance.

GOVERNMENT COMPLIANCE

Tested in accordance with UL-723.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	PE Coated Cloth
Adhesive	Natural Rubber/Resin
Adhesion to Steel (oz/in of width) PSTC-101	55 (15 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	20 (87.5 N/25mm)
Elongation (% at break)	18
Total Thickness (mils) PSTC-133	10.0 (0.25 mm)
Temperature Resistance	+32°F ~ +160°F (0°C ~ +71°C)
Color	Silver



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 8/13