

Y2560

DOUBLE-COATED UPVC FILM TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

2.0 mil UPVC film coated on both sides with pressure-sensitive acrylic adhesive. Provides exceptional shear strength, good adhesion and high initial tack allowing immediate/permanent bond to a variety of surfaces including surfaces such as metal, wood, glass, cement and plastics. Features an easy release 3 mil glassine paper liner (gold).

Product is not repulpable.

PRODUCT APPLICATION

Fastening of nameplates, trophy, luggage tags, wooden trim, signs, etc. Fastening of decorative trims (e.g. PVC profile, stainless steel and plastic parts) and any application that requires the joining of two surfaces.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	2 mil (50.8μ) UPVC
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	88 (2.5 kg/25mm)
Elongation (% @ Break) PSTC-131	150 (MD) / 120 (CD)
Total Thickness w/o Liner (mils) PSTC-133	8.3 (0.21mm)
Shear Adhesion to Steel (hours) 1" x 1" x 1 kg @ 77°F (25°C) PSTC-107	>72
Service Temperature (Short Term)	-22°F to +194°F (-30°C to +90°C)
Color	White



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/15

