### **T227**

# SINGLE LINER MEDIUM TACK BLASTLITE

#### INTERTAPE POLYMER GROUP®

## **TECHNICAL DATA SHEET**

#### **DESCRIPTION**

IPG's answer to vinyl. Specially formulated rubber provides impact resistance and natural flexibility allowing T227 to conform tightly around curves and uneven surfaces. Medium-tack rubber adhesive bonds quickly to clean surfaces. Uniform thickness, high quality, conformable, long-lasting, and easy to use. Release-treated paper liner permits easy tear by hand. Un-punched/friction fed. Can also be cut by knife for precise fit. Unlike vinyl, T227 does not contain PVC and can be safely cut using laser method.

#### **PRODUCT APPLICATION**

Protection of polished granite or marble, primed/painted wood, and HDU foam board during sandblasting, etching and carving processes.

#### **STANDARD SIZES**

25" x 10 yds Also available in slit goods

#### **STORAGE & SHELF LIFE**

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

# While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes

without notice or obligation in our products and publications.

EFFECTIVE: 12/22

#### **NOMINAL VALUES**

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

**Adhesive** Medium Tack / Rubber

**Total Thickness** (mil) 28 (0.71 mm)

PSTC-133

**Tensile Strength** (lbs/in) 5.5 (24.09 N/25mm)

PSTC-131

**180° Adhesion to Steel** (oz/in) 50 (13.69 N/25mm)

PSTC-101

**Elongation** (% at break) 450

PSTC-131

**Punch** Unpunched, Hand Cut

**Liner Color** White

